



## TECHNICAL DOCUMENTATION FOR SOLID FUEL LOCAL SPACE HEATER

According to:

Commission Regulation (EU) 2015/1185 of 24 April 2015 implementing Directive 2009/125/EC of the European Parliament and of the Council Commission Delegated Regulation (EU) 2015/1186 supplementing Directive 2010/30/EU of the European Parliament and of the Council

Model identifier				<b>KAWMET HARITA S15i ECO</b>							
Indirect heating functionality				no							
Direct heat output				6,5 (kW)							
Indirect heat output				N.A. (kW)							
FUEL	PREFERRED FUEL	OTHER SUITABLE FUEL(S)	$\eta_s$ [%]	SPACE HEATING EMISSIONS AT NOMINAL HEAT OUTPUT (*)				SPACE HEATING EMISSIONS AT MINIMUM HEAT OUTPUT (**)			
				PM	OGC	CO	NO <sub>x</sub>	PM	OGC	CO	NO <sub>x</sub>
				[x] mg/Nm <sup>3</sup> (13 % O <sub>2</sub> )				[x] mg/Nm <sup>3</sup> (13 % O <sub>2</sub> )			
Wood logs with moisture content ≤ 25 %	yes	no	70,3	35	103	1386	110				
Compressed wood with moisture content < 12 %	no	no									
Other woody biomass	no	no									
Non-woody biomass	no	no									
Anthracite and dry steam coal	no	no									
Hard coke	no	no									
Low temperature coke	no	no									
Bituminous coal	no	no									
Lignite briquettes	no	no									
Peat briquettes	no	no									
Blended fossil fuel briquettes	no	no									
Other fossil fuel	no	no									
Blended biomass and fossil fuel briquettes	no	no									
Other blend of biomass and solid fuel	no	no									
<b>CHARACTERISTICS WHEN OPERATING WITH THE PREFERRED FUEL</b>											
Seasonal space heating energy efficiency $\eta_s$ [%]								70,3			
Energy Efficiency Index (EEI) [%]								106			
ITEM	SYMBOL	VALUE	UNIT	ITEM				SYMBOL	VALUE	UNIT	
<b>HEAT OUTPUT</b>				<b>USEFUL EFFICIENCY (NCV AS RECEIVED)</b>							
Nominal heat output	P <sub>nom</sub>	6,5	kW	Useful efficiency at nominal heat output				$\eta_{th, nom}$	80,3	%	
Minimum heat output (indicative)	P <sub>min</sub>	N.A.	kW	Useful efficiency at minimum heat output (indicative)				$\eta_{th, min}$	N.A.	%	
<b>AUXILIARY ELECTRICITY CONSUMPTION</b>				<b>TYPE OF HEAT OUTPUT / ROOM TEMPERATURE CONTROL</b>							
At nominal heat output	e <sub>l, max</sub>	x,xxx	kW	single stage heat output, no room temperature control				yes			
At minimum heat output	e <sub>l, min</sub>	x,xxx	kW	two or more manual stages, no room temperature control				no			
In standby mode	e <sub>l, sb</sub>	x,xxx	kW	with mechanic thermostat room temperature control				no			
				with electronic room temperature control				no			
				with electronic room temperature control plus day timer				no			
				with electronic room temperature control plus week timer				no			
				<b>OTHER CONTROL OPTIONS (MULTIPLE SELECTIONS POSSIBLE)</b>							
				room temperature control, with presence detection				no			
				room temperature control, with open window detection				no			
				with distance control option				no			
<b>PERMAMENT PILOT FLAME POWER REQUIREMENT</b>											
Pilot flame power requirement (if applicable)	P <sub>pilot</sub>	N.A.	kW								
Contact details	ODLEWNIA KAW-MET MAREK KAWIŃSKI Sp.z o.o. / ZADĄBROWIE 311 / 37-716 / ORŁY / POLAND +48 166 72 48 10 / info@kawmet.pl										
(*) PM = particulate matter, OGC = organic gaseous compounds, CO = carbon monoxide, NO <sub>x</sub> = nitrogen oxides (**) Only required if correction factors F(2) or F(3) are used.											
The technical documentation was prepared on the basis of the results of tests carried out by the Oil and Gas, provided in test reports No. Nr 4226 A2 24 / 4226 B2 24. Notified Body No. 1450.											

 Zadąbrowie 25.07.2024  
 Date and place

**ODLEWNIA "KAW-MET"**  
**MAREK KAWIŃSKI SP. Z O.O.**  
 37-716 Orły, Zadąbrowie 311  
 NIP 7952568415, REGON 521473146

Signed for and on behalf of the manufacturer by:  
 CEO Marek Kawiński